



AFS

SERIES

ALL STAINLESS STEEL FLOOR SCALE





Erosion Proof Version,
Stands for Harsh Environment

COMMON FEATURES

- OIML-R76 and EC Class III Type Approved
- All Stainless Steel Housing, Platform and Pillar
- Sealed Indicator
- Wash Down Design According to IP65
- Waterproof Sophisticated Tactile Keyboard
- Flexible Platform Collocation
- Two Platform Structures Available for Different Operating Environment-
Wash Down Version: Aluminum Load Cell and Aluminum Alloy Load Receiving Structure
Erosion Proof Version: Stainless Steel Load Cell and Load Receiving Structure
- User Programmable Capacity and Division
- Equipped with Power On Zero Tracking, Re-zero, Auto Calibration, Auto Power Saving, Digital Motion Filtering Device, Auto Tare, Accumulation Memory and Dual Interval Selection**
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: 200 Hours Plus
- Complete with Low Battery and Charging Status Indicator
- 5 1/2 x 51mm Wide Angle LCD Display
- Adjustable Feet, Rechargeable Battery, Power Adaptor, Bubble Level and Indicator Dust Cover Included

**Depends on R60 approval grade of the load cell used

DISPLAY RESOLUTION; - OIML APPLICATIONS

- Standard = 3000
- Maximum = 30000 Under Extended Display Mode

DISPLAY RESOLUTION; - NON-OIML APPLICATIONS

- User Programmable
- Recommended = 6000 to 7500
- Maximum = 30000

OPTION AVAILABLE

- EL Backlight
- RS232C Interface

SPECIFICATIONS

Model No.	Capacity	Recommended Display Resolution		Platform
		OIML Application	Non-OIML Application	
AFS-60	60kg	0.02kg	0.01kg	All Stainless Steel 425 x 525mm
AFS-150	150kg	0.05kg	0.02kg	
AFS-300	300kg	0.1kg	0.05kg	
AFS-60II	60kg	0.02kg	0.01kg	All Stainless Steel Load Cell & Load Receiving Structure 425 x 525mm
AFS-150II	150kg	0.05kg	0.02kg	
AFS-300II	300kg	0.1kg	0.05kg	
AFS-L210II	210kg	0.1kg	0.05kg	All Stainless Steel Load Cell & Load Receiving Structure 500 x 600mm
AFS-L420II	420kg	0.2kg	0.1kg	
Tare Range	OIML = 1/3 Max - e Non-OIML = Full Range			
Power Source	By Built-in Rechargeable Battery or AC/DC Power Adaptor			
Operating Environment	0° - 40°C (32° - 104°F), Non-condensed R.H. ≤ 85%			

Specifications subject to change without notice



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Sheng Road Hsin Tien City 231 Taipei Hsien Taiwan R.O.C.
Tel. +886-2-2918121 (12 Lines) Fax +886-2-29181508-29183652-29112176-7
http://www.uwe-scale.com.tw e-mail:uwe@ms8.hinet.net

Oct '2002 Designed by DARY
Printed in Taiwan