

Features

- **Applications:** Powder weighing, Jewelry weighing, Laboratory & Chemistry weighing
- **Loadcell:** High precision single point Alum. load cell, resolution up to 1/30,000
- **Construction:** Compact ABS housing
Stainless steel platter
Includes precision calibration / check weight for EPS-302
Adjustable feet and leveling bubble for quick set up before using
Constructed with RS232 interface to communicate with PC
- **Indicator:** LCD display with blue backlight makes reading easy-to-review in even dim light
4 functional keys: On/Off, Unit, Mode, Tare
- **Functions:** Weighing, Stability, Overload and underload indicators,
Low battery indicator, Automatic shut off



Specifications

Item	Parameters	
Capacity	EPS-302	EPS-3001
	300gx0.01g	3000gx0.1g
Platform Size	Φ120mm	140x140mm
Scale Dimensions	136mm (L)x96mm(W)x52mm(H) / 5.35"(L)x3.78"(W)x2.05"(H)	
Packing	380mmx345mmx450mm/20pcs/ctn	
Shipping Weight	G.W.: 11kg N.W.: 10kg	
Units of measure	g, oz, ct, ozt, dwt, gn	
Display	0.3"(7.5mm) high, 8 segments, 5 digits LCD	
Power	6VDC 500mA adapter or 4xAAA batteries	
Operation Temp	0°C to 40°C (32°F to 104°F)	
Options	AC adapter, calibration weights, plastic pan	