PH3

Waterproof *IP68*
Check-weighing Indicator

EXCELL®
Since 1979

ISO9001 CE RoHS WEEE Compliant OIML

PH3

IP68 Waterproof Check-weighing Indicator

IP68

Features:

- IP68 waterproof check-weighing indicator with 304 stainless steel housing.
- Two adjustable weighing speed: moderate and slow.
- Selectable weighing units: Kilogram(kg), gram(g), pound(lb), and ounce(oz).
- Hi/Lo/OK meter & relay output (max. 10A, 120VAC or 5A, 250VAC).
- Up to 1/30,000 display resolution.
- 10 preset settings, Percentage display, Limit/Target operation modes, Pre-tare function, Net/Gross function, Auto backlight, Auto power-off timer.
- Auto calibration, Auto zero tracking, Power-saving feature, and Low power indication.
- Adjustable digital filter to suppress weighing fluctuations caused by environmental vibrations.
- Low power warning and charging/discharging protection.
- Can be integrated with weighing platforms of different sizes and capacities for high flexibility in weighing system customization.
- Built-in bi-directional RS-232.

Option:

- Relay card(3 output sets)

Specifications:

170mm

90mm

256mm

Operating Temperature:	-10°C ~ 40°C (14°F ~ 104°F)
Power Source:	AC 100V~240V (±10％) DC 12V adapter + DC 6V / 4Ah rechargeable battery
Dimensions:	256 x 170 x 90mm
Display:	LCD 6 digits, 25mm height, LED backlight